



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Flexible Marine Nautica IMO FF

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035
Fax: 504-841-0036
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620
Fax: 619-234-2432

Description:

Flexible Marine Nautica IMO FF blanket is a thermal insulation with a 2 mil Foil Facing that provides an excellent vapor retardant. The base blanket and Foil Facing meet U.S. Coast Guard's stringent IMO requirements. It is generally installed behind sheathing.

Installation is with insulation pins and clips, and joints can be covered with a U.S.C.G. approved, self stick foil tape.

<i>Specifications:</i>	U.S. Coast Guard: 164.109/164.112
<i>Standard Sizes:</i>	1" x 48" x 100' (400 sf/roll) 1-1/2" x 48 x 100 *400 sf/roll 2" x 48" x 100' (400 sf/roll) 3" x 48" x 100' (400 sf/roll)
<i>Weight:</i>	1": .063 lbs/sf 1-1/2: .094 lbs/sf 2": .125 lbs/sf 3": .188 lbs/sf

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.

Base Blanket: Nominal .75 pcf Fiberglass Blanket

Facing: 2 mil aluminum foil
Color: silver
Flame Spread/
Smoke: Meets Part 2 of the FTP Code

Thermal

Conductivity: .23@75°F Temp (BTU-IN/SF/°F/HR)
R-Factor: 4.35 per inch thickness