



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035

Fax: 504-841-0036

E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620

Fax: 619-234-2432

Flexible Marine Nautica IMO FF

Description:

Flexible Marine Nautica IMO FF blanket is a thermal insulation with a 2 mil Foil Facing that provides an excellent vapor barrier. The base blanket and Foil Facing meet U.S. Coast Guard's stringent IMO requirements. It is generally installed behind sheathing.

Installation is with insulation pins and clips, and joints can be covered with a U.S.C.G. approved, self stick foil tape.

Specifications: U.S. Coast Guard: 164.109/164.112

Standard Sizes: 1" x 48" x 100' (400 sf/roll)
2" x 48" x 100' (400 sf/roll)
3" x 48" x 100' (400 sf/roll)

Weight: 1": .177 lbs/sf
2": .22 lbs/sf
3": .30 lbs/sf

Base Blanket: 1" - Nominal 1.5 pcf Fiberglass Blanket
2" & 3" - Nominal 1.0 pcf Fiberglass Blanket

Facing: 2 mil aluminum foil
Color: silver
Flame Spread/
Smoke: Meets Part 2 of the FTP Code

Thermal

Conductivity: .23@75°F Temp (BTU-IN/SF/°F/HR)
R-Factor: 4.35 per inch thickness

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.