



# IMO / US Navy Certified Insulations

## RB, L.L.C.

Insulation with integrity, from people who care.

### Nautica IMO FF Mineral Wool Board

Main Branch:

PO Box 23781  
New Orleans, La 70183  
www.rblc.com

Phone: 504-841-0035  
Fax: 504-841-0036  
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street  
San Diego, Ca 92113

Phone: 619-234-2620  
Fax: 619-234-2432

Description:

Nautica Mineral Wool Insulation with IMO FF combines fire performance with a 2 mil Foil Facing that provides an excellent vapor retardant. It is approved by the U.S. Coast Guard for structural fire protection. The board is generally installed behind sheathing or joiner bulkheads.

Installation is with insulation pins and clips, and joints can be covered with a USCG approved, self-stick adhesive foil tape.

|                 |   |
|-----------------|---|
| Specifications: | U.S. Coast Guard: 164.107 / 164.109 / 164.112   |
| Standard Sizes: | 1" x 24" x 48" (96 sf/ctn) (Wrap for A-60 Deck)<br>1-1/2" x 24" x 48" (64 sf/ctn) (Wrap for A-60 B/H)<br>2" x 24" x 48" (48 sf/ctn) (A-60 Decks)<br>3" x 24" x 48" (32 sf/ctn) (A-60 Bulkheads) |

Base Board: 7A# Mineral Wool Board

Facing: 2 mil aluminum foil

Color: Silver

Flame Spread/  
Smoke: Meets Part 2 of the FTP Code

Thermal Conductivity: .24@75°F Temp (BTU-IN/SF/°F/HR)

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.