



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035
Fax: 504-841-0036
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620
Fax: 619-234-2432

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.

Nautica IMO PFG Acoustic Board

Description:

Nautica IMO PFG acoustic board is an excellent sound absorbing fiberglass hullboard with a perforated glass cloth facing that provides both a tough, paintable finish, yet allows sound to be easily absorbed. The grooves allow the board to be painted without loss of acoustic value. It is approved by both the U.S. Navy (MIL-A-23054 Mod.) and the U.S. Coast Guard for thermal and acoustic treatments in ships. It can also be used in mechanical rooms in commercial buildings.

Installation is with insulation pins and clips, and joints can be covered with fiberglass lagging tape.

Specifications:	U.S. Coast Guard: 164.109/164.112 U.S. Navy: MIL-A-23054 (Modified)
Standard Sizes:	1" x 24" x 48" (160 sf/ctn) 2" X 24" 48" (80 sf/ctn)
Weight:	1": .34 lbs/sf 2": .58 lbs/sf

Base Board:	Nominal 3 pcf Fiberglass Board
Facing:	Glass cloth, 12.8 oz/square yard
Color:	White
	MIL-C-20079 Type I, Cl. 2
	Perforated 1/2" O.C.
Flame Spread/	
Smoke:	Meets Part 2 of the FTP Code
Thermal Conductivity:	.23@75°F Temp (BTU-IN/SF/°F/HR)

Sound Absorption Coefficients

Freq	125	250	500	1000	2000	4000	NRC
2"	.31	.90	1.21	1.17	.97	.80	1.05