



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Nautica IMO PFW Acoustic Board

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035

Fax: 504-841-0036

E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620

Fax: 619-234-2432

Description:

Nautica PFW Perforated Acoustic Board is a fiberglass board with a white, perforated glass cloth facing. It consists of 3 pcf base hullboard, laminated to a heavy density "waffle" board. The waffle matches the perforations in the cloth facing.

Installation is with insulation pins and clips, and joints can be covered with fiberglass lagging tape. The perforated face may be painted without affecting the acoustic properties of the insulation.

Specifications:	U.S. Navy:	MIL-A-23054
Standard Sizes:	1" x 24" x 48" (160 sf/ctn)	
	2" X 24" 48" (80 sf/ctn)	
Weight:	1":	.52 lbs/sf
	2":	.76 lbs/sf

Base Board: Nominal 3 pcf Fiberglass Board

Waffle Board: Nominal 12 pcf molded fibrous glass

Facing: Glass cloth, 12.8 oz/square yard

Color: White

MIL-C-20079 Type I, Cl. 2

Perforated 1/2" O.C.

Flame Spread/

Smoke: Passes MIL-A-23054

Thermal Conductivity: .23@75°F Temp (BTU-IN/SF/°F/HR)

Acoustic Absorption: 1" NRC=.65

2" NRC=.80

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.