



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035
Fax: 504-841-0036
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620
Fax: 619-234-2432

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.

Nautica Fiberglass Lagging Tape

Description:

Nautica Fiberglass Lagging Tapes are made of non-combustible glass fibers. The unusually high tensile strength of the fibers allow them to be used as a thin, lightweight tape to secure tight, well-fitting insulation seams with minimum labor.

The tape meets USCG 164.109 and MIL-C-20079S Type II, Class 1.

The tape is applied with adhesives/coatings meeting MIL-A-3316, Class 1, Grade A and/or adhesives meeting USCG 164.109.

Specifications:	U.S. Coast Guard: 164.109 U.S. Navy: MIL-C-20079 Type II, CI 1
Standard Sizes:	2" x 150 LF 3" x 150 LF 4" x 150 LF 6" x 150 LF

Color:	White
Weight:	6 oz/square yard
Weave:	Plain
Finish:	Plain
Fiber:	75 1/0
Count:	44 x 32
Thickness:	.007"
Breaking Strength:	
Warp:	250 lb.f./in.
Fill:	250 lb.f./in.