



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Nautica TA-301 VBD Duct Insulation

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035
Fax: 504-841-0036
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620
Fax: 619-234-2432

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.

Description:

Nautica TA-301 VBD is a light weight, fire resistant duct insulation with a high performance vapor retardant facing.

The basic construction consists of a baseboard of Solimide polyimide foam, faced with an aluminized polyester/aluminum foil laminate, with an integral fiberglass scrim for reinforcement.

It is installed on round, oval or rectangular ducts, secured with adhesive and/or stud fasteners. All joints and penetrations are sealed with tape. The facing has been primed for painting, or may be left as is.

Specifications:	U.S. Navy: base material DOD-I-24688 Type I NAVSEA SER 03M3/021
Standard Sizes:	1 x 24 x 48 (160 sf/carton) 2 x 24 x 48 (80 sf/carton)
Weight:	1" .10 lbs/sf 2" .14 lbs/sf

Base Board: Solimide TA-301 Polyimide foam per DOD-I-24688,
0.4 pcf density

Facing: Reinforced aluminized polyester/aluminum foil laminate
with prime coated surface with glass fiber mesh
reinforcing.

Fire Resistance: ASTM-E-162 Flame Spread: 1.00
ASTM-E-662 Smoke Density,
Flaming: 1.5
Non-Flaming: 3.2
Passed NAVSEA Quarter Scale Room Test

Water Vapor Transmission: ASTM-E96-90 .03 Perm inch

Thermal Conductivity: .30@75°F Temp (BTU-IN/SF/°F/HR)