



IMO / US Navy Certified Insulations

RB, L.L.C.

Insulation with integrity, from people who care.

Main Branch:

PO Box 23781
New Orleans, La 70183
www.rblc.com

Phone: 504-841-0035
Fax: 504-841-0036
E-mail: sales@rblc.com

San Diego Branch:

1995 Main Street
San Diego, Ca 92113

Phone: 619-234-2620
Fax: 619-234-2432

All statements herein are expressions of opinion that we believe to be true and reliable. However, they are represented without guaranty or warranty. Statements regarding the use of our products for their use alone or in conjunction with any other materials should not be intended as recommendations. Nothing herein is intended to infringe on any patents. No patent warranty of any kind, express or implied is hereby made.

Nautica TA-301 VBD-CF Insulation

Description:

Inherently fire resistant, this light weight insulation was developed for significant weight reduction of thermal insulation for the U.S. Navy. The polyimide foam, Solimide TA-301 is approximately 1/6th the weight of traditional fiberglass insulation. It is approved by the U.S. Navy for insulation on pipe and equipment up to 370°F. It is also used to insulate HVAC ducts.

VBD Facing is a three-ply laminate of aluminum foil, fiberglass scrim re-inforcing and heat sealable metalized polyester film. It provides a highly fire resistive, excellent vapor retardant finish or jacket over insulation boards and pipe insulations. It is also prime coated to accept paint.

VBD-CF is a combination of the above VBD, laminated to a fiberglass fabric (MIL-C-20079, Type I, Class 2) for additional abuse resistance where required.

Specifications:	U.S. Navy: DOD-I-24688 Type I
Standard Sizes:	1 x 24 x 48 (160 sf/carton) 2 x 24 x 48 (80 sf/carton)
Weight:	1" .16 lbs/sf 2" .26 lbs/sf

Base Board: Solimide TA-301 Polyimide foam per DOD-I-24688,
Type I— 0.4 pcf density

Facing: VBD: 3 ply laminate of aluminum foil, glass scrim and
aluminized polyester— Permeability: .02 Perms

Glass Cloth: 12.8 oz/yd², MIL-C-20079 Type I, Class 2